

according to UK REACH Regulation

ACECUT 5503 cutting fluid

Revision date: 14.09.2022 Product code: BO5002825 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ACECUT 5503 cutting fluid

Further trade names

BO 50028051, 1 I BO 5002805, 5 I BO 5002825, 30 I BO 5002835, 200 I

UFI: D4SG-M0YP-A00J-AP5H

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

cutting fluid

1.3. Details of the supplier of the safety data sheet

Company name: BOHLE AG
Street: Dieselstr. 10
Place: 42781 Haan
Telephone: +49 2129 5568-0

Telephone: +49 2129 5568-0 Telefax: +49 2129 5568-282

e-mail: info@bohle.de

Contact person: Dr. Martin Schade Telephone: +49 2129 5568-300

e-mail: MSDS@bohle.de Internet: www.bohle.com

Responsible Department: Chemie

1.4. Emergency telephone Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories:

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Decane

Hydrocarbons, C11-C14, n-alkane, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C11-C14, isoalkanes, <2% aromatics

Signal word: Danger

Pictograms:



Hazard statements

H304 May be fatal if swallowed and enters airways.



according to UK REACH Regulation

ACECUT 5503 cutting fluid

Revision date: 14.09.2022 Product code: BO5002825 Page 2 of 9

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P331 Do NOT induce vomiting.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container to hazardous or special waste collection point.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains (R)-p-mentha-1,8-diene, d-limonene. May produce an allergic reaction.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Hydrocarbons

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP F	Regulation)			
64742-47-8	Hydrocarbons, C11-C14	n-alkane, isoalkanes, cyclics, <2%	aromatics	< 50 %	
	926-141-6		01-2119456620-43		
	Asp. Tox. 1; H304				
1174522-15-6	Hydrocarbons, C11-C14	isoalkanes, cyclics, <2% aromatic	s	< 25 %	
	927-285-2		01-2119480162-45		
	Asp. Tox. 1; H304 EUH0	66	·		
	Hydrocarbons, C11-C14		< 25 %		
	920-901-0		01-2119456810-40		
	Asp. Tox. 1; H304 EUH0	·			
124-18-5	Decane	< 15 %			
	204-686-4		01-2119474199-26		
	Flam. Liq. 3, Asp. Tox. 1				
5131-66-8	3-butoxypropan-2-ol, pro	< 10 %			
	225-878-4	603-052-00-8	01-2119475527-28		
	Skin Irrit. 2, Eye Irrit. 2; H				
5989-27-5	(R)-p-mentha-1,8-diene,	< 1 %			
	227-813-5	601-029-00-7	01-2119529223-47		
	Flam. Liq. 3, Skin Irrit. 2, H400 H410				

Full text of H and EUH statements: see section 16.



Safety Data Sheet

according to UK REACH Regulation

ACECUT 5503 cutting fluid

Revision date: 14.09.2022 Product code: BO5002825 Page 3 of 9

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. L	imits, M-factors and ATE		
64742-47-8	926-141-6	Hydrocarbons, C11-C14, n-alkane, isoalkanes, cyclics, <2% aromatics	< 50 %	
	dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg			
1174522-15-6	927-285-2	Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics	< 25 %	
	inhalation: LC50 = >5000 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg			
5989-27-5	227-813-5	(R)-p-mentha-1,8-diene, d-limonene	< 1 %	
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg			

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

Move out of dangerous area.

Take off contaminated clothing and shoes immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

If symptoms persist, call a physician.

After contact with skin

Wash off with soap and plenty of water.

If symptoms persist, call a physician.

After contact with eyes

Rinse thoroughly with plenty of water, also under the eyelids. Remove contact lenses, if present and easy to

do. Continue rinsing.

Consult a physician.

After ingestion

Rinse mouth thoroughly with water.

Do NOT induce vomiting.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.

@1501.B015620

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2)

Extinguishing powder

alcohol resistant foam

Water spray jet

Unsuitable extinguishing media

high volume water jet

5.2. Special hazards arising from the substance or mixture

Heating or fire can release toxic gas.

Carbon dioxide, Carbon monoxide

5.3. Advice for firefighters



Safety Data Sheet

according to UK REACH Regulation

ACECUT 5503 cutting fluid

Revision date: 14.09.2022 Product code: BO5002825 Page 4 of 9

Standard procedure for chemical fires.

Self-contained respirator (breathing apparatus)

Additional information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

Do not allow to enter into soil/subsoil.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Other information

Provide adequate ventilation.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Dispose of waste according to applicable legislation.

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations.

To avoid risks to man and the environment, comply with the instructions for use.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Usual measures for fire prevention.

Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Do not breathe vapours or spray mist.

Avoid contact with skin, eyes and clothing. Take off all contaminated clothing immediately.

Wash hands before breaks and immediately after handling the product.

When using do not eat or drink. Do not smoke.

Keep away from food, drink and animal feedingstuffs.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store in a place accessible by authorized persons only.

Protect from direct sunlight.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)



according to UK REACH Regulation

ACECUT 5503 cutting fluid

Revision date: 14.09.2022 Product code: BO5002825 Page 5 of 9

cutting fluid

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
5131-66-8	5131-66-8 3-butoxypropan-2-ol, propylene glycol monobutyl ether					
Worker DNEL,	long-term	dermal	systemic	44 mg/kg bw/day		
Worker DNEL,	long-term	inhalation	systemic	270,5 mg/m³		
5989-27-5	5989-27-5 (R)-p-mentha-1,8-diene, d-limonene					
Worker DNEL, long-term		inhalation	systemic	33,3 mg/m³		
Worker DNEL,	long-term	dermal	local	0,222 mg/cm ²		

PNEC values

CAS No	Substance		
Environmental compartment		Value	
5131-66-8 3-butoxypropan-2-ol, propylene glycol monobutyl ether			
Freshwater		0,525 mg/l	
Marine water		0,0525 mg/l	
Freshwater sediment		2,36 mg/kg	
Marine sediment		0,236 mg/kg	
Soil		0,16 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber), NBR (Nitrile rubber)

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

EN 13034 (type 6 limited splash-tight)

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Combination filtering device Respirator with filter for organic vapour, Recommended Filter type: A-P2

Environmental exposure controls

Do not flush into surface water or sanitary sewer system.

Do not allow to enter into soil/subsoil.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.



Safety Data Sheet

according to UK REACH Regulation

ACECUT 5503 cutting fluid

Revision date: 14.09.2022 Product code: BO5002825 Page 6 of 9

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: colourless

Odour: like: Hydrocarbons

Test method

Changes in the physical state

Melting point/freezing point: < -20 °C
Boiling point or initial boiling point and > 180 °C

boiling range:

Flash point: 63 °C ISO 2719

Lower explosion limits: 0,4 vol. % Upper explosion limits: 7 vol. %

Auto-ignition temperature: > 270 °C DIN 51794

Self-ignition temperature not auto-flammable

pH-Value (at 5-7 °C):

Viscosity / dynamic: 2 mPa·s DIN 54453

(at 20 °C)

Viscosity / kinematic: < 2 mm²/s

(at 40 °C)

Water solubility: insoluble
Vapour pressure: <2 hPa

(at 20 °C)

Density (at 20 °C): 0,77 g/cm³ DIN 51757

9.2. Other information

Other safety characteristics

Vapours may form explosive mixtures with air.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from direct sunlight.

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

No decomposition if used as directed.

SECTION 11: Toxicological information



according to UK REACH Regulation

ACECUT 5503 cutting fluid

Revision date: 14.09.2022 Product code: BO5002825 Page 7 of 9

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
64742-47-8	Hydrocarbons, C11-C14, n-alkane, isoalkanes, cyclics, <2% aromatics						
	oral	LD50 mg/kg	>5000	Rat	OECD 401		
	dermal	LD50 mg/kg	>5000	Rabbit	OECD 402		
1174522-15- 6	Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics						
	oral	LD50 mg/kg	>5000	Rat			
	dermal	LD50 mg/kg	>5000	Rabbit			
	inhalation (4 h) vapour	LC50 mg/l	>5000	Rat			
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene						
	oral	LD50 mg/kg	> 5000	Rat	GESTIS		
	dermal	LD50 mg/kg	> 5000	Rabbit	GESTIS		

Irritation and corrosivity

May cause eye irritation with susceptible persons.

Sensitising effects

Contains: (R)-p-Mentha-1,8-dien. This substance is classified as hazardous according to Regulation (EC) No 1272 (2008). sensitising

11.2. Information on other hazards

Other information

@1501.B015620

SECTION 12: Ecological information

12.1. Toxicity

This product has no known eco-toxicological effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene						
	Acute fish toxicity	LC50	0,7 mg/l	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50 mg/l	0,42	48 h	Daphnia magna		

12.3. Bioaccumulative potential

Bioaccumulation is unlikely.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene	4,23

12.4. Mobility in soil

No data available



Safety Data Sheet

according to UK REACH Regulation

ACECUT 5503 cutting fluid

Revision date: 14.09.2022 Product code: BO5002825 Page 8 of 9

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not flush into surface water or sanitary sewer system.

Avoid subsoil penetration.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Contaminated packaging

Dispose of completely emptied containers as combustible waste or metal waste depending on the material.

SECTION 14: Transport information

Marine transport (IMDG)

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Other applicable information

Not dangerous goods in the meaning of ADR/RID, ADNR, IMDG-Code, ICAO/IATA-DGR

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC): 100%

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2.

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.



for adhering to existing laws and regulations.

Safety Data Sheet

according to UK REACH Regulation

	ACECUT 5503 cutting fluid	
Revision date: 14.09.2022	Product code: BO5002825	Page 9 of 9
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH066	Repeated exposure may cause skin dryness or cracking.	
EUH208	Contains (R)-p-mentha-1,8-diene, d-limonene. May produce an allergic reaction.	
Further Information		
	used on the present level of our knowledge. It does not, however, give assurance of and establishes no contract legal rights. The receiver of our product is singularly responsible	

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)