Telefax: +49 2129 5568-282



# **Safety Data Sheet**

according to UK REACH Regulation

# **Xtragrip MS Polymer**

Revision date: 25.10.2023 Product code: BO5730005 Page 1 of 7

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Xtragrip MS Polymer

#### Further trade names

BO 5730005, 290 ml BO 5730006, 25 x 290 ml

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# Use of the substance/mixture

adhesive

### 1.3. Details of the supplier of the safety data sheet

Company name: BOHLE AG
Street: Dieselstr. 10
Place: D-42781 Haan
Telephone: +49 2129 5568-0

e-mail: info@bohle.de

Contact person: Dr. Martin Schade Telephone: +49 2129 5568-300

e-mail: MSDS@bohle.de Internet: www.bohle.com

Responsible Department: Chemie

1.4. Emergency telephone Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

number:

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

# **GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

#### 2.2. Label elements

# Hazard components for labelling

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

# Chemical characterization

adhesive

Print date: 25.10.2023



# **Safety Data Sheet**

according to UK REACH Regulation

# **Xtragrip MS Polymer**

Revision date: 25.10.2023 Product code: BO5730005 Page 2 of 7

### **Hazardous components**

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (GB CLP Regulation	n)	•			
-	reaction mass of N,N'-ethane1,2-diylbis(hexanamide) and 12-hydroxy-N-[2- [(1-oxyhexyl)amino]ethyl]octadecanamide and N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan amide)					
	432-430-3	616-200-00-1				
	Aquatic Chronic 4; H413					
2768-02-7	trimethoxyvinylsilane; trimethoxy(vinyl)silane					
	220-449-8	014-049-00-0	01-2119513215-52			
	Flam. Liq. 3, Acute Tox. 4, Skin Sens. 1B, STOT RE 2; H226 H332 H317 H373					
1760-24-3	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane					
	Eye Dam. 1, Skin Sens. 1; H318 H317					
54068-28-9	Dioctylbis(pentan-2,4-dionato-O,O')zinn					
	Skin Sens. 1, STOT SE 2; H317 H371					
52829-07-9	Bis(2,2,6,6-tetramethyl-4-piperidyl)sebacat					
	Repr. 2, Eye Dam. 1, Aquatic Acute 1; H361f H318 H400					

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. I	Specific Conc. Limits, M-factors and ATE		
2768-02-7	220-449-8	trimethoxyvinylsilane; trimethoxy(vinyl)silane		
	inhalation: LC50 = 16,8 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 3259 mg/kg; oral: LD50 = 7120 mg/kg			

### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

No special measures are necessary.

# After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

### After ingestion

Rinse mouth. Call a doctor if you feel unwell.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

### Suitable extinguishing media

Carbon dioxide (CO2), Extinguishing powder, Water spray jet, alcohol resistant foam

# 5.2. Special hazards arising from the substance or mixture

Carbon monoxide, Hydrogen chloride (HCI)

# 5.3. Advice for firefighters

Standard procedure for chemical fires.

# **SECTION 6: Accidental release measures**

### 6.3. Methods and material for containment and cleaning up



according to UK REACH Regulation

# **Xtragrip MS Polymer**

Revision date: 25.10.2023 Product code: BO5730005 Page 3 of 7

#### Other information

Use mechanical handling equipment.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

# Advice on safe handling

None under normal processing.

When using, do not eat, drink or smoke.

Wash hands before breaks and after work.

### Advice on general occupational hygiene

See section 7. No additional measures necessary.

# 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Store in a dry place. Store in a closed container.

### Hints on joint storage

Keep away from heat and sources of ignition. Keep away from: oxidizing agents

# Further information on storage conditions

Protect from frost, heat and sunlight.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

### **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
2768-02-7	trimethoxyvinylsilane; trimethoxy(vinyl)silane			
Worker DNEL,	long-term	inhalation	systemic	2,6 mg/m³
Worker DNEL,	long-term	dermal	systemic	0,2 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	2,6 mg/m³
Worker DNEL, acute		dermal	systemic	0,2 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,7 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,1 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,1 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	0,7 mg/m³
Consumer DNEL, acute		dermal	systemic	0,1 mg/kg bw/day

# **PNEC** values

CAS No	Substance			
Environmenta	Environmental compartment			
2768-02-7	trimethoxyvinylsilane; trimethoxy(vinyl)silane			
Freshwater 0,36 mg/				
Freshwater (intermittent releases)		2,4 mg/l		
Marine water		0,036 mg/l		
Freshwater sediment		1,3 mg/kg		
Marine sediment		0,13 mg/kg		
Soil		0,055 mg/kg		



according to UK REACH Regulation

# **Xtragrip MS Polymer**

Revision date: 25.10.2023 Product code: BO5730005 Page 4 of 7

### 8.2. Exposure controls

# Appropriate engineering controls

Provide adequate ventilation.

#### Individual protection measures, such as personal protective equipment

### Eye/face protection

Not required

### Hand protection

rubber gloves.

### Skin protection

safety glasses with side-shields conforming to EN166

# Respiratory protection

Not required

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Paste
Colour: light grey
Odour: characteristic

Test method

Water solubility: insoluble

Solubility in other solvents

miscible with most organic solvents

Density (at 20 °C): 1,6 g/cm<sup>3</sup>

# 9.2. Other information

# Information with regard to physical hazard classes

Explosive properties

Not explosive

Self-ignition temperature not auto-flammable

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

# 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

# 10.5. Incompatible materials

Oxidising agent

### 10.6. Hazardous decomposition products

Heating or fire can release toxic gas. (Carbon monoxide, Hydrogen chloride (HCI))

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

#### **Acute toxicity**

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

# Xtragrip MS Polymer

Revision date: 25.10.2023 Product code: BO5730005

Page 5 of 7

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
2768-02-7	trimethoxyvinylsilane; trir	trimethoxyvinylsilane; trimethoxy(vinyl)silane						
	oral	LD50 mg/kg	7120	Rat		OECD 401		
	dermal	LD50 mg/kg	3259	Rabbit		OECD 402		
	inhalation (4 h) vapour	LC50	16,8 mg/l	Rat		OECD 403		
	inhalation dust/mist	ATE	1,5 mg/l					

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
2768-02-7	trimethoxyvinylsilane; trim	trimethoxyvinylsilane; trimethoxy(vinyl)silane						
	Acute fish toxicity	LC50	191 mg/l		Oncorhynchus mykiss (Rainbow trout)			
	Acute crustacea toxicity	EC50 mg/l	168,7		Daphnia magna (Big water flea)			
	Crustacea toxicity	NOEC mg/l	28,1		Daphnia magna (Big water flea)		OECD 211	

# 12.2. Persistence and degradability

CAS No	Chemical name						
	Method Value d Source						
	Evaluation						
2768-02-7	trimethoxyvinylsilane; trimethoxy(vinyl)silane						
	OECD 301F	51 %	28				

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# **SECTION 13: Disposal considerations**



according to UK REACH Regulation

# **Xtragrip MS Polymer**

Revision date: 25.10.2023 Product code: BO5730005 Page 6 of 7

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Can be incinerated together with household waste in compliance with applicable technical regulations following consultation with approved waste disposal management companies and authorities in charge. Discharge into the environment must be avoided.

### List of Wastes Code - residues/unused products

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants other than those mentioned in 08 04 09

List of Wastes Code - used product

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants other than those mentioned in 08 04 09

List of Wastes Code - contaminated packaging

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); plastic packaging

### **SECTION 14: Transport information**

Land transport (ADR/RID)

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

<u>14.2. UN proper shipping name:</u> No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

<u>14.2. UN proper shipping name:</u> No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

2004/42/EC (VOC): < 2,6%

< 41,8 g/l

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

#### **SECTION 16: Other information**

### Changes

This data sheet contains changes from the previous version in section(s): 2.



according to UK REACH Regulation

**Xtragrip MS Polymer** 

Revision date: 25.10.2023	Product code: BO5730005	Page 7 of 7
Relevant H and EUH sta	tements (number and full text)	
H226	Flammable liquid and vapour.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H332	Harmful if inhaled.	
H361f	Suspected of damaging fertility.	
H371	May cause damage to organs.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H413	May cause long lasting harmful effects to aquatic life.	

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)