

according to Regulation (EC) No 1907/2006

**ACELUB I lubricant**

Revision date: 07.06.2017

Product code: BO5002808

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

ACELUB I lubricant

**Further trade names**

BO 5002808, 30 I

BO 5002838, 200 I

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricant and lubricant additive

**1.3. Details of the supplier of the safety data sheet**

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	D-42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Klaus Nehren	Telephone: +49 2129 5568-276
e-mail:	MSDS@bohle.de	
Internet:	www.bohle-group.com	
Responsible Department:	Chemie	

**1.4. Emergency telephone number:** Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 3

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C11-C14, isoalkanes, cyclics, &lt;2% aromatics

**Signal word:** Danger**Pictograms:****Hazard statements**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe Aerosol / vapour.

P262 Do not get in eyes, on skin, or on clothing.

according to Regulation (EC) No 1907/2006

**ACELUB I lubricant**

Revision date: 07.06.2017

Product code: BO5002808

Page 2 of 9

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P308	IF exposed or concerned:
P310	Immediately call a POISON CENTER/doctor.
P501	Dispose of this material and its container to hazardous or special waste collection point.

**Special labelling of certain mixtures**

EUH066 Repeated exposure may cause skin dryness or cracking.

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Chemical characterization**

Solvent

**Hazardous components**

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
	Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics	25-50%
	927-285-2	01-2119480162-45
	Asp. Tox. 1; H304 EUH066	
	Hydrocarbons, C11-C14, isoalkanes, <2% aromatics	25-50%
	920-901-0	01-2119456810-40
	Asp. Tox. 1; H304 EUH066	
124-18-5	Decane	10-25%
	204-686-4	01-2119474199-26
	Flam. Liq. 3, Asp. Tox. 1; H226 H304 EUH066	
5131-66-8	3-butoxypropan-2-ol, propylene glycol monobutyl ether	5-10%
	225-878-4	603-052-00-8
	01-2119475527-28	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319	

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

First aider: Pay attention to self-protection!  
 Move out of dangerous area.  
 Take off contaminated clothing and shoes immediately.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.  
 If symptoms persist, call a physician.

**After contact with skin**

Wash off with soap and plenty of water.  
 If symptoms persist, call a physician.

**After contact with eyes**

Rinse thoroughly with plenty of water, also under the eyelids. Remove contact lenses, if present and easy to do. Continue rinsing.

according to Regulation (EC) No 1907/2006

**ACELUB I lubricant**

Revision date: 07.06.2017

Product code: BO5002808

Page 3 of 9

Consult a physician.

**After ingestion**

Rinse mouth thoroughly with water.  
Do NOT induce vomiting.  
Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

May be fatal if swallowed and enters airways.  
Repeated exposure may cause skin dryness or cracking.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>)  
Extinguishing powder  
alcohol resistant foam  
Water spray jet

**Unsuitable extinguishing media**

high volume water jet

**5.2. Special hazards arising from the substance or mixture**

Heating or fire can release toxic gas.  
Carbon dioxide, Carbon monoxide

**5.3. Advice for firefighters**

Standard procedure for chemical fires.  
Self-contained respirator (breathing apparatus) (DIN EN 133)

**Additional information**

Use water spray to cool unopened containers.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment.

**6.2. Environmental precautions**

Do not flush into surface water or sanitary sewer system.  
Do not allow to enter into soil/subsoil.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

Provide adequate ventilation.  
Prevent spread over a wide area (e.g. by containment or oil barriers).  
Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Dispose of waste according to applicable legislation.

**6.4. Reference to other sections**

Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation as well as local exhaustion at critical locations.

according to Regulation (EC) No 1907/2006

## ACELUB I lubricant

Revision date: 07.06.2017

Product code: BO5002808

Page 4 of 9

To avoid risks to man and the environment, comply with the instructions for use.

### Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Usual measures for fire prevention.  
 Take precautionary measures against static discharges.  
 Vapours can form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.  
 Store in a place accessible by authorized persons only.  
 Protect against direct sunlight.

#### Advice on storage compatibility

Do not store together with oxidizing agents

#### Further information on storage conditions

Recommended storage temperature: 5 - 40°C

### 7.3. Specific end use(s)

cutting fluid

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
5131-66-8	3-butoxypropan-2-ol, propylene glycol monobutyl ether			
Worker DNEL, long-term		dermal	systemic	44 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	270,5 mg/m <sup>3</sup>

#### PNEC values

CAS No	Substance	Value
5131-66-8	3-butoxypropan-2-ol, propylene glycol monobutyl ether	
Freshwater		0,525 mg/l
Marine water		0,0525 mg/l
Freshwater sediment		2,36 mg/kg
Marine sediment		0,236 mg/kg
Soil		0,16 mg/kg

### 8.2. Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

#### Protective and hygiene measures

Do not breathe vapours or spray mist.  
 Avoid contact with skin, eyes and clothing. Take off all contaminated clothing immediately.  
 Wash hands before breaks and immediately after handling the product.  
 When using do not eat or drink. Do not smoke.  
 Keep away from food, drink and animal feedingstuffs.

#### Eye/face protection

safety glasses with side-shields conforming to EN166

according to Regulation (EC) No 1907/2006

**ACELUB I lubricant**

Revision date: 07.06.2017

Product code: BO5002808

Page 5 of 9

**Hand protection**

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber), NBR (Nitrile rubber)

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

**Skin protection**

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

DIN EN 13034 (Type 6 limited splash-tight)

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment. Combination filtering device (EN 14387)

Respirator with filter for organic vapour, Recommended Filter type: A-P2

**Environmental exposure controls**

Do not flush into surface water or sanitary sewer system.

Do not allow to enter into soil/subsoil.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	colourless
Odour:	like: Hydrocarbons

pH-Value: not applicable

**Test method****Changes in the physical state**

Melting point: < -20 °C

Initial boiling point and boiling range: >180 °C

Flash point: 58 °C ISO 2719

Lower explosion limits: 0,4 vol. %

Upper explosion limits: 7 vol. %

Ignition temperature: >270 °C DIN 51794

**Auto-ignition temperature**

not auto-flammable

Vapour pressure:  
(at 20 °C) <2 hPa

Density: 0,75 g/cm<sup>3</sup> DIN 51757

Water solubility: insoluble

Viscosity / dynamic:  
(at 20 °C) 2 mPa·s DIN 54453

Viscosity / kinematic:  
(at 40 °C) <2 mm<sup>2</sup>/s

**9.2. Other information**

Vapours can form explosive mixtures with air.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No dangerous reaction known under conditions of normal use.

according to Regulation (EC) No 1907/2006

**ACELUB I lubricant**

Revision date: 07.06.2017

Product code: BO5002808

Page 6 of 9

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Vapours may form explosive mixtures with air.

**10.4. Conditions to avoid**

Heat, flames and sparks.

Keep away from open flames, hot surfaces and sources of ignition.

**10.5. Incompatible materials**

oxidizing agents

**10.6. Hazardous decomposition products**

No decomposition if used as directed.

**SECTION 11: Toxicological information**
**11.1. Information on toxicological effects**
**Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
5131-66-8	3-butoxypropan-2-ol, propylene glycol monobutyl ether				
	oral	LD50 mg/kg	>2000	Rat	OECD 423
	dermal	LD50 mg/kg	>2000	Rat	OECD 402

**Irritation and corrosivity**

May cause eye irritation with susceptible persons.

**Practical experience**
**Other observations**

Repeated exposure may cause skin dryness or cracking.

**SECTION 12: Ecological information**
**12.1. Toxicity**

This product has no known eco-toxicological effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
5131-66-8	3-butoxypropan-2-ol, propylene glycol monobutyl ether					
	Acute fish toxicity	LC50 mg/l	>100	96 h	Pimephales promelas (fathead minnow)	
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna (Big water flea)	

**12.3. Bioaccumulative potential**

Bioaccumulation is unlikely.

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ACELUB I lubricant**

Revision date: 07.06.2017

Product code: BO5002808

Page 7 of 9

**12.6. Other adverse effects**

slightly water endangering  
Do not flush into surface water or sanitary sewer system.  
Avoid subsoil penetration.


**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Advice on disposal**

Can be incinerated, when in compliance with local regulations.


**Contaminated packaging**

Dispose of completely emptied containers as combustible waste or metal waste depending on the material.

**SECTION 14: Transport information**
**Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN 3295
<b>14.2. UN proper shipping name:</b>	HYDROCARBONS, LIQUID, N.O.S. (Low boiling point hydrogen treated naphtha, Naphtha (petroleum), hydrodesulfurized heavy)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
	
Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number:</b>	UN 3295
<b>14.2. UN proper shipping name:</b>	HYDROCARBONS, LIQUID, N.O.S. (Low boiling point hydrogen treated naphtha, Naphtha (petroleum), hydrodesulfurized heavy)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
	
Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1

**Marine transport (IMDG)**

<b>14.1. UN number:</b>	UN 3295
<b>14.2. UN proper shipping name:</b>	HYDROCARBONS, LIQUID, N.O.S. (Low boiling point hydrogen treated naphtha, Naphtha (petroleum), hydrodesulfurized heavy)
<b>14.3. Transport hazard class(es):</b>	3

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ACELUB I lubricant

Revision date: 07.06.2017

Product code: BO5002808

Page 8 of 9

**14.4. Packing group:**

III

Hazard label:

3



Marine pollutant:

no

Special Provisions:

223

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number:**

UN 3295

**14.2. UN proper shipping name:**

HYDROCARBONS, LIQUID, N.O.S. (Low boiling point hydrogen treated naphtha, Naphtha (petroleum), hydrodesulfurized heavy)

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

III

Hazard label:

3



Special Provisions:

A3 A224

Limited quantity Passenger:

10 L

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:

355

IATA-max. quantity - Passenger:

60 L

IATA-packing instructions - Cargo:

366

IATA-max. quantity - Cargo:

220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:

no

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D):

1 - slightly water contaminating

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

## SECTION 16: Other information

**Relevant H and EUH statements (number and full text)**

H226

Flammable liquid and vapour.

H304

May be fatal if swallowed and enters airways.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

EUH066

Repeated exposure may cause skin dryness or cracking.



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ACELUB I lubricant**

Revision date: 07.06.2017

Product code: BO5002808

Page 9 of 9

**Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*