

# Lugo

Hinges for one side opening doors



# Lugo

## Hinges for one side opening doors

An all-rounder for the most diverse bathroom styles - that is how Lugo can be defined. Thanks to its modern and classic design, the high quality, all-brass range of fittings fits perfectly into any bathroom design. Its straight-lined design with slightly rounded-off edges makes Lugo an elegant classic. Technical fixings and screws are concealed behind a cover, achieving a clear and unobtrusive design. In addition, the flush installation enables easy cleaning.

The rise and fall function offers enhanced comfort - the door fittings close automatically, smoothly and silently. Lugo is therefore the ideal choice for use in barrier-free shower applications.

The Lugo fitting range is suitable for 6 mm and 8 mm glass. Maximum door weight 36 kg, max. door size 900 x 2000 mm.




Abb. BO 52/0002


# Lugo

## Possible installation options


### » Recess installation




Pivot door as recess application



2 pivot doors as recess application




Pivot door with fixed glazing as recess application




Pivot door with fixed glazing as recess application


### » Corner installation




Pivot door with sidelight




Pivot door with fixed glazing and sidelight




2 pivot doors as corner application



Pivot door on fixed glazing + pivot door on wall as corner application




Pivot door on fixed glazing with sidelight




Corner entry with 2 pivot doors


### » Corner application with shortened sidelight



Pivot door with shortened sidelight



Pivot door on fixed glazing with shortened sidelight




Pivot door with fixed glazing and shortened sidelight

## Lugo Shower Door Hinge, glass/wall 90°, opens outwards, DIN left







FINISH	ART. NO.
shiny chrome-plated	BO 5240000

max. door weight per pair	36 kg
max. door height	2000 mm
max. door width	900 mm
Material	brass



**i** Glass thickness 6, 8 mm · lifting height 5 mm · The door is kept closed by magnetic seals. Lugo shower door fittings must always be mounted together with sealing strips, which can be guided through the hinge. In order to avoid the incorrect operation of the door (opening against the opening direction), sealing strips and, if necessary, a stop should be used.




## Lugo Shower Door Hinge, glass/wall 90°, opens outwards, DIN right







FINISH	ART. NO.
shiny chrome-plated	BO 5240001

max. door weight per pair	36 kg
max. door height	2000 mm
max. door width	900 mm
Material	brass



**i** Glass thickness 6, 8 mm · lifting height 5 mm · The door is kept closed by magnetic seals. Lugo shower door fittings must always be mounted together with sealing strips, which can be guided through the hinge. In order to avoid the incorrect operation of the door (opening against the opening direction), sealing strips and, if necessary, a stop should be used.








## Lugo Shower Door Hinge, glass/glass 180°, opens outwards, DIN left



FINISH	ART. NO.
shiny chrome-plated	BO 5240002

max. door weight per pair	36 kg
max. door height	2000 mm
max. door width	900 mm
Material	brass

**i** Glass thickness 6, 8 mm · lifting height 5 mm · The door is kept closed by magnetic seals. Lugo shower door fittings must always be mounted together with sealing strips, which can be guided through the hinge. In order to avoid the incorrect operation of the door (opening against the opening direction), sealing strips and, if necessary, a stop should be used.








## Lugo Shower Door Hinge, glass/glass 180°, opens outwards, DIN right



FINISH	ART. NO.
shiny chrome-plated	BO 5240003

max. door weight per pair	36 kg
max. door height	2000 mm
max. door width	900 mm
Material	brass

**i** Glass thickness 6, 8 mm · lifting height 5 mm · The door is kept closed by magnetic seals. Lugo shower door fittings must always be mounted together with sealing strips, which can be guided through the hinge. In order to avoid the incorrect operation of the door (opening against the opening direction), sealing strips and, if necessary, a stop should be used.






## Lugo Shower Door Hinge, glass/glass 135°, opens outwards, DIN left



FINISH	ART. NO.
shiny chrome-plated	BO 5240004
max. door weight per pair	36 kg
max. door height	2000 mm
max. door width	900 mm
Material	brass

**i** Glass thickness 6, 8 mm · lifting height 5 mm · The door is kept closed by magnetic seals. Lugo shower door fittings must always be mounted together with sealing strips, which can be guided through the hinge. In order to avoid the incorrect operation of the door (opening against the opening direction), sealing strips and, if necessary, a stop should be used.






## Lugo Shower Door Hinge, glass/glass 135°, opens outwards, DIN right



FINISH	ART. NO.
shiny chrome-plated	BO 5240005
max. door weight per pair	36 kg
max. door height	2000 mm
max. door width	900 mm
Material	brass

**i** Glass thickness 6, 8 mm · lifting height 5 mm · The door is kept closed by magnetic seals. Lugo shower door fittings must always be mounted together with sealing strips, which can be guided through the hinge. In order to avoid the incorrect operation of the door (opening against the opening direction), sealing strips and, if necessary, a stop should be used.



## Lugo Corner Clamp, glass/wall 90°



FINISH


ART. NO.

shiny chrome-plated



BO 5240006

Material

brass



**i** Glass thickness 6, 8 mm



## Lugo Corner Clamp, glass/glass 90°



FINISH


ART. NO.

shiny chrome-plated



BO 5240007

Material

brass



**i** Glass thickness 6, 8 mm



**Bohle Ltd.**  
Fifth Avenue  
Tameside Park, Dukinfield  
Cheshire, SK16 4PP

T +44 161 3421100  
F +44 161 3440111

[info@bohle.ltd.uk](mailto:info@bohle.ltd.uk)

