

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1. Product identifier

UV Adhesive VERIFIX B 682-T

Further trade names

BO 5209393, 20 g

BO 5209394, 100 g

BO 5209395, 250 g / BO 5209395S, Spacer, 250 g

BO 5209396, 1000 g / BO 5209396S, Spacer, 1000 g

UFI: ANHR-4WGH-WK6C-FRM1

1.2. Relevant identified uses of the substance or mixture and uses advised against
1.3. Details of the supplier of the safety data sheet

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	D-42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Dr. Martin Schade	Telephone: +49 2129 5568-300
e-mail:	MSDS@bohle.de	
Internet:	www.bohle.com	
Responsible Department:	Chemie	

1.4. Emergency telephone number: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification
2.1. Classification of the substance or mixture
Regulation (EC) No 1272/2008

Skin Irrit. 2; H315

Eye Dam. 1; H318

Skin Sens. 1; H317

STOT SE 3; H335

Aquatic Acute 1; H400

Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements
Regulation (EC) No 1272/2008
Hazard components for labelling

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate

2-hydroxyethyl methacrylate

acrylic acid, prop-2-enoic acid

tert-butyl perbenzoate

maleic acid

Signal word: Danger

Pictograms:


Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 2 of 13

Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Methacrylate/Acrylate resin(s).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 3 of 13

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate			<50 %
	227-561-6		01-2119957862-25	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H315 H319 H317 H335 H400 H410			
73324-00-2	Urethane acrylate			<25 %
	615-966-4		-	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			
868-77-9	2-hydroxyethyl methacrylate			<25 %
	212-782-2	607-124-00-X	01-2119490169-29	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317			
24650-42-8	2,2-dimethoxy-1,2-diphenylethan-1-one			<8,9 %
	246-386-6		01-2120000336-73	
	Acute Tox. 4, STOT RE 2, Aquatic Chronic 3; H302 H373 H412			
79-10-7	acrylic acid, prop-2-enoic acid			<5 %
	201-177-9	607-061-00-8	01-2119452449-31	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Aquatic Acute 1; H226 H332 H312 H302 H314 H400			
614-45-9	tert-butyl perbenzoate			<1 %
	210-382-2		01-2119513317-46	
	Org. Perox. C, Acute Tox. 4, Skin Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 3; H242 H332 H315 H317 H400 H412			
110-16-7	maleic acid			<1 %
	203-742-5	607-095-00-3	01-2119488705-25	
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H302 H315 H319 H317 H335			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
5888-33-5	227-561-6	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	<50 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
868-77-9	212-782-2	2-hydroxyethyl methacrylate	<25 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = 5050 mg/kg	
24650-42-8	246-386-6	2,2-dimethoxy-1,2-diphenylethan-1-one	<8,9 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = >1694 mg/kg	
79-10-7	201-177-9	acrylic acid, prop-2-enoic acid	<5 %
		inhalation: LC50 = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 1100 mg/kg; oral: LD50 = 500 mg/kg STOT SE 3; H335: >= 1 - 100 Aquatic Acute 1; H400: M=1	
614-45-9	210-382-2	tert-butyl perbenzoate	<1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 3817 mg/kg; oral: LD50 = 4838 mg/kg	
110-16-7	203-742-5	maleic acid	<1 %
		dermal: LD50 = 1560 mg/kg; oral: LD50 = 1090 mg/kg Skin Sens. 1; H317: >= 0,1 - 100	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 4 of 13

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection!
Get medical advice/attention if you feel unwell.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If symptoms persist, call a physician.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting. Immediately give large quantities of water to drink. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Irritation to respiratory tract
Skin contact : May cause an allergic skin reaction.
Eye contact : Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

water spray, dry powder, foam, carbon dioxide (CO₂)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Carbon monoxide, nitrogen oxides (NO_x)

5.3. Advice for firefighters

Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Wear personal protection equipment (refer to section 8).
Provide adequate ventilation.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.
Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up**Other information**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Ensure adequate ventilation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 5 of 13

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage
7.1. Precautions for safe handling
Advice on safe handling

Avoid contact with skin and eyes.

Do not eat, drink or smoke when using this product.

Ensure adequate ventilation.

Advice on protection against fire and explosion

No special technical protective measures required.

Advice on general occupational hygiene

Wash hands before breaks and after work. When using do not eat, drink or smoke.

Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

Further information on handling

Avoid: UV-radiation/sunlight

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up.

Recommended storage temperature 5 - 25°C. Keep away from direct sunlight.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
79-10-7	Acrylic acid	10	29		TWA (8 h)	
		20	59		STEL (1 min)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate			
	Worker DNEL, long-term	dermal	systemic	1,39 mg/kg bw/day
79-10-7	acrylic acid, prop-2-enoic acid			
	Worker DNEL, long-term	inhalation	systemic	30 mg/m ³
	Worker DNEL, acute	inhalation	systemic	30 mg/m ³
	Worker DNEL, long-term	inhalation	local	30 mg/m ³
	Worker DNEL, acute	inhalation	local	30 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 6 of 13

PNEC values

CAS No	Substance	Value
Environmental compartment		
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	
Freshwater		0,00092 mg/l
Marine water		0,000092 mg/l
Freshwater sediment		0,145 mg/kg
Marine sediment		0,0145 mg/kg
Micro-organisms in sewage treatment plants (STP)		2 mg/l
Soil		0,0285 mg/kg
79-10-7	acrylic acid, prop-2-enoic acid	
Freshwater		0,003 mg/l
Freshwater (intermittent releases)		0,0013 mg/l
Marine water		0,0003 mg/l
Freshwater sediment		0,0236 mg/kg
Marine sediment		0,00234 mg/kg

8.2. Exposure controls
Appropriate engineering controls

- Provide sufficient air exchange and/or exhaust in work rooms.
- Do not breathe vapour. To follow: Occupational exposure limit values

Individual protection measures, such as personal protective equipment
Eye/face protection

- safety glasses with side-shields conforming to EN166

Hand protection

- The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.
- Recommended material: NBR (Nitrile rubber), VITON
- Unsuitable material: Natural fibres (e.g. cotton)

Skin protection

- Wear suitable protective clothing.

Respiratory protection

- Usually no personal respiratory protection necessary. When using do not eat, drink or smoke.
- In case of inadequate ventilation wear respiratory protection. Full-/half-/quarter-face masks (EN 136/140)
- Respirator with filter for organic vapour. Recommended Filter type: A (P2)

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic

	Test method
Flash point:	> 100 °C
pH-Value (at 21 °C):	2,5 5% emulsion
Water solubility:	not determined
Density (at 25 °C):	1,1 g/cm ³

9.2. Other information
Information with regard to physical hazard classes

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 7 of 13

Explosive properties

None.

Other safety characteristics

Solvent content:

0,0%

Viscosity / dynamic:
(at 23 °C)

900 mPa·s

SECTION 10: Stability and reactivity**10.1. Reactivity**

Light / UV-radiation/sunlight

Oxidising agent, strong

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep cool. Protect from sunlight. Heat, flames and sparks.

In case of light influence: Polymerisation

10.5. Incompatible materialsReducing agent, strong. Oxidising agent, strong
strong acids and strong bases**10.6. Hazardous decomposition products**

No decomposition if stored and applied as directed.

Thermal decomposition can lead to the escape of irritating gases and vapours. Carbon monoxide (CO),
Carbon dioxide (CO₂), Hydrocarbons**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 8 of 13

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
868-77-9	2-hydroxyethyl methacrylate				
	oral	LD50 5050 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
24650-42-8	2,2-dimethoxy-1,2-diphenylethan-1-one				
	oral	LD50 >1694 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rat		
79-10-7	acrylic acid, prop-2-enoic acid				
	oral	LD50 500 mg/kg	Rat		
	dermal	LD50 1100 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 11 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
614-45-9	tert-butyl perbenzoate				
	oral	LD50 4838 mg/kg	Rat		
	dermal	LD50 3817 mg/kg	Rabbit		
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
110-16-7	maleic acid				
	oral	LD50 1090 mg/kg	Rat	OECD 401	
	dermal	LD50 1560 mg/kg	Rabbit		

SECTION 12: Ecological information
12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate					
	Acute fish toxicity	LC50 mg/l	0,704	96 h	Danio rerio (zebrafish)	OECD 203
	Crustacea toxicity	NOEC mg/l	0,092	21 d	Daphnia magna (Big water flea)	
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50	227 mg/l	96 h	Pimephales promelas	
24650-42-8	2,2-dimethoxy-1,2-diphenylethan-1-one					
	Acute fish toxicity	LC50	6 mg/l	96 h	Lepomis macrochirus (Bluegill)	
	Acute algae toxicity	ErC50 mg/l	0,17	72 h	Scenedesmus subspicatus	
	Acute bacteria toxicity	(EC50 mg/l)	>100	3 h	Activated sludge	
614-45-9	tert-butyl perbenzoate					
	Acute fish toxicity	LC50	1,6 mg/l	96 h	Danio rerio (zebrafish)	OECD 203
	Acute algae toxicity	ErC50	1,3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50	11 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202
110-16-7	maleic acid					
	Acute fish toxicity	LC50	75 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	74,35	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50 mg/l	42,81	48 h	Daphnia magna (Big water flea)	OECD 202

12.2. Persistence and degradability

CAS No	Chemical name		Method	Value	d	Source
			Evaluation			
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate			57%	28	
614-45-9	tert-butyl perbenzoate					
	aerob			70%	28	
	Readily biodegradable, according to appropriate OECD test.					

12.3. Bioaccumulative potential
Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	4,52
868-77-9	2-hydroxyethyl methacrylate	0,47
24650-42-8	2,2-dimethoxy-1,2-diphenylethan-1-one	3,42
79-10-7	acrylic acid, prop-2-enoic acid	0,35
614-45-9	tert-butyl perbenzoate	3
110-16-7	maleic acid	-1,3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 10 of 13

BCF

CAS No	Chemical name	BCF	Species	Source
110-16-7	maleic acid	<10		

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Consult the appropriate local waste disposal expert about waste disposal.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information
Land transport (ADR/RID)
14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (@5888.33.5Pan, @0079.10.7Pan)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 11 of 13

Tunnel restriction code:

-

Inland waterways transport (ADN)
14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (@5888.33.5Pan, @0079.10.7Pan)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Marine transport (IMDG)
14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate, acrylic acid,
 prop-2-enoic acid)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:



Special Provisions:

274, 335, 969

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-A, S-F

Air transport (ICAO-TI/IATA-DGR)
14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate, acrylic acid,
 prop-2-enoic acid)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:



Special Provisions:

A97 A158 A197

Limited quantity Passenger:

30 kg G

Passenger LQ:

Y964

Excepted quantity:

E1

IATA-packing instructions - Passenger:

964

IATA-max. quantity - Passenger:

450 L

IATA-packing instructions - Cargo:

964

IATA-max. quantity - Cargo:

450 L

14.5. Environmental hazards

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 12 of 13

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: @5888.33.5Pan, @0079.10.7Pan

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

 2004/42/EC (VOC): 0 %
0 g/l

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information
Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023

Product code: BO5209394

Page 13 of 13

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)