

according to UK REACH Regulation

Pyrosil Primer

Revision date: 04.05.2023 Product code: BO5209499 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Pyrosil Primer

Further trade names

BO 5209494, 50 ml, BO 5209490 SET, BO 5209491 SET

BO 5209498, 250 ml BO 5209499, 1000 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesives and/or sealants

1.3. Details of the supplier of the safety data sheet

Company name: BOHLE AG
Street: Dieselstr. 10
Place: D-42781 Haan
Telephone: 440,2420 EF68

Telephone: +49 2129 5568-0 Telefax: +49 2129 5568-282

e-mail: info@bohle.de

Contact person: Dr. Martin Schade Telephone: +49 2129 5568-300

e-mail: MSDS@bohle.de Internet: www.bohle.com

Responsible Department: Chemie

1.4. Emergency telephone Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.



according to UK REACH Regulation

Pyrosil Primer

Revision date: 04.05.2023 Product code: BO5209499 Page 2 of 9

P260 Do not breathe vapour / Aerosol.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P337+P313 If eye irritation persists: Get medical advice/attention.
P312 Call a POISON CENTER/doctor if you feel unwell.
P501 Dispose of waste according to applicable legislation.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No Index No REACH No			
	Classification (GB CLP Regulation)			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			90-100 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Conc. I	fic Conc. Limits, M-factors and ATE				
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol				
	inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 13400 mg/kg; oral: LD50 = 4570 mg/kg					

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing.

After inhalation

Move to fresh air. Consult a physician after significant exposure. If victim is unconscious but breathing: Victim to lie down in the recovery position, cover and keep him warm. Call a physician immediately.

After contact with skin

Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

After contact with eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists, consult a specialist.

After ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Give sodium sulfate as laxative (1 tablespoon in 1 glass of water) with plenty of activated coal.

4.2. Most important symptoms and effects, both acute and delayed

No information available.



according to UK REACH Regulation

Pyrosil Primer

Revision date: 04.05.2023 Product code: BO5209499 Page 3 of 9

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

water spray, alcohol-resistant foam, dry chemical, carbon dioxide (CO2)

Unsuitable extinguishing media

high volume water jet

5.2. Special hazards arising from the substance or mixture

In use may form flammable/explosive vapour-air mixture.

Fire may cause evolution of: Carbon monoxide, Carbon dioxide)

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Standard procedure for chemical fires.

Additional information

Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation.

Keep away from heat and sources of ignition.

Avoid contact with skin and eyes. Do not breathe vapour.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Other information

Provide adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations.

Provide room air exhaust at ground level.

Avoid formation of aerosol. Do not breathe vapour/aerosol.

Avoid contact with the skin and the eyes.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition. Do not smoke.



according to UK REACH Regulation

Pyrosil Primer

Revision date: 04.05.2023 Product code: BO5209499 Page 4 of 9

Advice on general occupational hygiene

Avoid contact with skin, eyes and clothing. Provide adequate ventilation. Take off all contaminated clothing immediately. Keep away from food, drink and animal feedingstuffs. When using do not eat or drink. Do not smoke. Wash hands before breaks and at the end of workday.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
67-63-0 propan-2-ol; isopropyl alcohol; isopropanol					
Consumer DNI	EL, long-term	oral	systemic	26 mg/kg bw/day	
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day	
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³	
Worker DNEL, long-term		inhalation	systemic	500 mg/m³	

PNEC values

CAS No	Substance			
Environment	al compartment	Value		
67-63-0	67-63-0 propan-2-ol; isopropyl alcohol; isopropanol			
Freshwater		140,9 mg/l		
Freshwater (intermittent releases)		140,9 mg/l		
Marine wate		140,9 mg/l		
Freshwater sediment		552 mg/kg		
Marine sediment		552 mg/kg		
Micro-organisms in sewage treatment plants (STP)		2251 mg/l		
Soil		28 mg/kg		

8.2. Exposure controls

Appropriate engineering controls

Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached. However it is the duty of the user to verify this and follow given exposure limits at the workplace.

Individual protection measures, such as personal protective equipment

Eye/face protection

safety glasses with side-shields conforming to EN166



according to UK REACH Regulation

Pyrosil Primer

Revision date: 04.05.2023 Product code: BO5209499 Page 5 of 9

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard

EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber) >=0,5mm, NBR (Nitrile rubber) >=0,35mm

Breakthrough time: >=480 min.

Skin protection

impervious clothing

Respiratory protection

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: clear
Odour: alcoholic

Test method

Boiling point or initial boiling point and 77-78 °C

boiling range:

Lower explosion limits: 2 vol. %
Upper explosion limits: 12 vol. %
Flash point: 12 °C
Auto-ignition temperature: 425 °C
pH-Value (at 20 °C): neutral
Water solubility: soluble
Vapour pressure: 48 hPa

(at 20 °C)

Density (at 20 °C): 0,79 g/cm³
Relative vapour density: 2

(at 20 °C)

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Self-ignition temperature not auto-flammable

Other safety characteristics

Solvent content: <100 % Viscosity / dynamic: 2,4 mPa·s

(at 20 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal processing.

10.2. Chemical stability

No decomposition if used as directed.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4. Conditions to avoid

Keep away from heat and sources of ignition.



according to UK REACH Regulation

Pyrosil Primer

Revision date: 04.05.2023 Product code: BO5209499 Page 6 of 9

10.5. Incompatible materials

strong acids and oxidizing agents

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
67-63-0	propan-2-ol; isopropyl alc	ohol; isopropanol	l			
	oral	LD50 457 mg/kg	70	Rat		
	dermal	LD50 134 mg/kg	100	Rabbit		
	inhalation (4 h) vapour	LC50 30 r	mg/l	Rat		

11.2. Information on other hazards

Other information

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol						
	Acute fish toxicity	LC50 mg/l	9640		Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 mg/l	>2000		Desmodesmus subspicatus		

12.2. Persistence and degradability

Readily biodegradable, according to appropriate OECD test.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	-0,16

12.4. Mobility in soil

The product evaporates readily.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.



according to UK REACH Regulation

Pyrosil Primer

Revision date: 04.05.2023 Product code: BO5209499 Page 7 of 9

Further information

Water hazard class 1: slightly water endangering

Do not let product enter drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

In accordance with local and national regulations.

List of Wastes Code - residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals

and chemical products not otherwise specified; other organic solvents, washing liquids and mother

liquors; hazardous waste

List of Wastes Code - used product

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals

and chemical products not otherwise specified; other organic solvents, washing liquids and mother

liquors; hazardous waste

List of Wastes Code - contaminated packaging

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); plastic packaging

Contaminated packaging

Non-contaminated packages may be recycled.

Contaminated packages must be completely emptied and can be re-used following proper cleaning.

cleaning agent : Water

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



according to UK REACH Regulation

Pyrosil Primer

Revision date: 04.05.2023 Product code: BO5209499 Page 8 of 9



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity:

Excepted quantity:

E2

EmS:

F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:UN 121914.2. UN proper shipping name:Isopropanol

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity Passenger:

1 L

Passenger LQ:

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

none

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Print date: 04.05.2023



Safety Data Sheet

according to UK REACH Regulation

Pyrosil Primer

Revision date: 04.05.2023 Product code: BO5209499 Page 9 of 9

2004/42/EC (VOC): >95 weight-%. VOC value 760

Subcategory according to Directive

2004/42/EC:

Preparatory and cleaning - Preparatory, VOC limit value: 850 g/l

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Flam. Liq. 2; H225	On basis of test data	
Eye Irrit. 2; H319	Calculation method	
STOT SE 3; H336	Calculation method	

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)