Telefax: +49 2129 5568-282



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VERIFIX 2K-60 Comp.B

Revision date: 05.07.2023 Product code: BO5500540B Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VERIFIX 2K-60 Comp.B

Further trade names

BO 5500540 = 25ml BO 5500540A + 25 ml BO 5500540B

Product group: Zulieferprodukt

UFI: TXTH-3T8E-3283-N82R

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: BOHLE AG
Street: Dieselstr. 10
Place: D-42781 Haan

Telephone: +49 2129 5568-0

e-mail: info@bohle.de

Contact person: Dr. Martin Schade Telephone: +49 2129 5568-300

e-mail: MSDS@bohle.de Internet: www.bohle.com

Responsible Department: Chemie

1.4. Emergency telephone Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Methyl methacrylate

2-hydroxyethyl methacrylate

2-methylpropenoic acid, methacrylic acid

1-Benzoyl-2-ethylimidazol

Signal word: Danger

Pictograms:







Hazard statements

H225 Highly flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.



according to Regulation (EC) No 1907/2006

VERIFIX 2K-60 Comp.B

Revision date: 05.07.2023 Product code: BO5500540B Page 2 of 10

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Methacrylate/Acrylate resin(s).

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulation (EC) N	lo 1272/2008)	·		
80-62-6	Methyl methacrylate			<50 %	
	201-297-1	607-035-00-6	01-2119452498-28		
	Flam. Liq. 2, Skin Irrit. 2, Skin Se	ns. 1, STOT SE 3; H225 H3	15 H317 H335		
868-77-9	2-hydroxyethyl methacrylate	< 50 %			
	212-782-2	607-124-00-X	01-2119490169-29		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sen				
79-41-4	2-methylpropenoic acid, methaci	<20 %			
	201-204-4	607-088-00-5	01-2119463884-26		
	Acute Tox. 4, Acute Tox. 4, Skin				
614-23-3	Benzoyl Thiourea	<10 %			
	Acute Tox. 4; H302				
	1-Benzoyl-2-ethylimidazol	<3 %			
	Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H318 H317 H412				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Cond	Limits, M-factors and ATE	
80-62-6	201-297-1	Methyl methacrylate	<50 %
	inhalation: L0	C50 = 78 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = 7900 mg/kg	
868-77-9	212-782-2	2-hydroxyethyl methacrylate	< 50 %
	dermal: LD50) = >5000 mg/kg; oral: LD50 = 5050 mg/kg	
79-41-4	201-204-4	2-methylpropenoic acid, methacrylic acid	<20 %
	inhalation: LC50 = >3,6 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg; oral: LD50 = 1320 mg/kg STOT SE 3; H335: >= 1 - 100		
614-23-3		Benzoyl Thiourea	<10 %
	oral: ATE = 5	00 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures



according to Regulation (EC) No 1907/2006

VERIFIX 2K-60 Comp.B

Revision date: 05.07.2023 Product code: BO5500540B Page 3 of 10

General information

First aider: Pay attention to self-protection! Get medical advice/attention if you feel unwell.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If symptoms persist, call a physician.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting. Immediately give large quantities of water to drink. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Irritation to respiratory tract

Skin contact: May cause an allergic skin reaction. Eye contact: Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

water spray, dry powder, foam, carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Carbon monoxide, nitrogen oxides (NOx)

5.3. Advice for firefighters

Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear personal protection equipment (refer to section 8).

Provide adequate ventilation.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Other information

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Ensure adequate ventilation.

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13



according to Regulation (EC) No 1907/2006

VERIFIX 2K-60 Comp.B

Revision date: 05.07.2023 Product code: BO5500540B Page 4 of 10

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid contact with skin and eyes.

Do not eat, drink or smoke when using this product.

Ensure adequate ventilation.

Advice on protection against fire and explosion

No special technical protective measures required.

Advice on general occupational hygiene

Wash hands before breaks and after work. When using do not eat, drink or smoke.

Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

Further information on handling

Avoid: UV-radiation/sunlight

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up.

Recommended storage temperature 5 - 25°C. Keep away from direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
79-41-4	Methacrylic acid	20	70		TWA (8 h)	
		40	140		STEL (15 min)	
80-62-6	Methyl methacrylate	50	-		TWA (8 h)	
		100	-		STEL (15 min)	

8.2. Exposure controls

Appropriate engineering controls

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapour. To follow: Occupational exposure limit values

Individual protection measures, such as personal protective equipment

Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Recommended material: NBR (Nitrile rubber), VITON Unsuitable material: Natural fibres (e.g. cotton)

Skin protection

Wear suitable protective clothing.

Respiratory protection

Usually no personal respirative protection necessary. When using do not eat, drink or smoke.

In case of inadequate ventilation wear respiratory protection. Full-/half-/quarter-face masks (EN 136/140)

Respirator with filter for organic vapour. Recommended Filter type: A (P2)



according to Regulation (EC) No 1907/2006

VERIFIX 2K-60 Comp.B

Revision date: 05.07.2023 Product code: BO5500540B Page 5 of 10

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: pink

Odour: characteristic

Boiling point or initial boiling point and 101 °C

boiling range:

Flash point: 10 °C Viscosity / kinematic: 5000 mm²/s

(at 23 °C)

Water solubility: not determined Vapour pressure: 47 hPa

(at 20 °C)

Density (at 25 °C): 1 g/cm³

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

None.

Other safety characteristics

Solvent content: 0,0%
Solid content: 100%
Viscosity / dynamic: 5000 mPa·s (at 25 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Light / UV-radiation/sunlight Oxidising agent, strong

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep cool. Protect from sunlight. Heat, flames and sparks.

In case of light influence: Polymerisation

10.5. Incompatible materials

Reducing agent, strong. Oxidising agent, strong strong acids and strong bases

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

Thermal decomposition can lead to the escape of irritating gases and vapours. Carbon monoxide (CO),

Carbon dioxide (CO2), Hydrocarbons

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



according to Regulation (EC) No 1907/2006

VERIFIX 2K-60 Comp.B

Revision date: 05.07.2023 Product code: BO5500540B Page 6 of 10

Acute toxicity

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
80-62-6	Methyl methacrylate							
	oral	LD50 mg/kg	7900	Rat				
	dermal	LD50 mg/kg	>5000	Rabbit	OECD 402			
	inhalation (4 h) vapour	LC50	78 mg/l	Rat				
868-77-9	2-hydroxyethyl methacrylate							
	oral	LD50 mg/kg	5050	Rat				
_	dermal	LD50 mg/kg	>5000	Rabbit				
79-41-4	2-methylpropenoic acid, methacrylic acid							
	oral	LD50 mg/kg	1320	Rat		OECD 401		
	dermal	ATE mg/kg	1100					
	inhalation (4 h) dust/mist	LC50	>3,6 mg/l	Rat		OECD 403		
614-23-3	Benzoyl Thiourea							
	oral	ATE mg/kg	500					

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
80-62-6	Methyl methacrylate							
	Acute fish toxicity	LC50	283 mg/l	96 h	Lepomis macrochirus (Bluegill)			
	Acute algae toxicity	ErC50	110 mg/l		Pseudokirchneriella subcapitata	OECD 201		
	Acute crustacea toxicity	EC50	69 mg/l		Daphnia magna (Big water flea)			
868-77-9	2-hydroxyethyl methacrylate							
	Acute fish toxicity	LC50	227 mg/l	96 h	Pimephales promelas			
79-41-4	2-methylpropenoic acid, methacrylic acid							
	Acute fish toxicity	LC50 mg/l	100-180	96 h	Danio rerio (zebrafish)		OECD 203	
	Acute crustacea toxicity	EC50 mg/l	>130	48 h	Daphnia magna (Big water flea)		OECD 202	

12.2. Persistence and degradability



according to Regulation (EC) No 1907/2006

VERIFIX 2K-60 Comp.B

Revision date: 05.07.2023 Product code: BO5500540B Page 7 of 10

CAS No	Chemical name						
	Method	Value	d	Source			
	Evaluation						
80-62-6	Methyl methacrylate						
	aerob	94%	14				
	Readily biodegradable (according to OECD criteria).						
79-41-4	2-methylpropenoic acid, methacrylic acid						
	OECD 301D 86%						
	Readily biodegradable (according to OECD criteria).						

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	Methyl methacrylate	1,38
868-77-9	2-hydroxyethyl methacrylate	0,47

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Consult the appropriate local waste disposal expert about waste disposal.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances: hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1133

Page 8 of 10



Revision date: 05.07.2023

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VERIFIX 2K-60 Comp.B Product code: BO5500540B

14.2. UN proper shipping name:

Adhesives (Methyl methacrylate, 2-methylpropenoic acid, methacrylic

acid)

14.3. Transport hazard class(es): 3 Ш 14.4. Packing group: Hazard label: 3



Classification code: Limited quantity: 5 L Excepted quantity: E1 Transport category: 3 Tunnel restriction code: Ε

Inland waterways transport (ADN)

14.1. UN number or ID number: **UN 1133**

14.2. UN proper shipping name: Adhesives (Methyl methacrylate, 2-methylpropenoic acid, methacrylic

acid)

14.3. Transport hazard class(es): 3 Ш 14.4. Packing group: Hazard label: 3



Classification code: F1 Limited quantity: 5 L Excepted quantity: F1

Marine transport (IMDG)

14.1. UN number or ID number: **UN 1133**

14.2. UN proper shipping name: Adhesives (Methyl methacrylate, Methacrylic acid)

14.3. Transport hazard class(es): Ш 14.4. Packing group: Hazard label: 3



Special Provisions: 223, 955 Limited quantity: 5 I Excepted quantity: E1 F-E, S-D EmS:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: **UN 1133**

14.2. UN proper shipping name: Adhesives (Methyl methacrylate, Methacrylic acid)

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 3



Special Provisions: A3 Limited quantity Passenger: 10 I Passenger LQ: Y344



according to Regulation (EC) No 1907/2006

VERIFIX 2K-60 Comp.B

Product code: BO5500540B Revision date: 05.07.2023 Page 9 of 10

Excepted quantity: E1

355 IATA-packing instructions - Passenger: 60 L IATA-max. quantity - Passenger: 366 IATA-packing instructions - Cargo: IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC): 0 %

0 g/l

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

2 - obviously hazardous to water Water hazard class (D):

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2.

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

	•
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of



according to Regulation (EC) No 1907/2006

VERIFIX 2K-60 Comp.B

Revision date: 05.07.2023 Product code: BO5500540B Page 10 of 10

processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)