

according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

UV Adhesive VERIFIX B 682-T

Further trade names

BO 5209393, 20 g BO 5209394, 100 g

BO 5209395, 250 g / BO 5209395S, Spacer, 250 g BO 5209396, 1000 g / BO 5209396S, Spacer, 1000 g UFI: ANHR-4WGH-WK6C-FRM1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesive

1.3. Details of the supplier of the safety data sheet

Company name: BOHLE AG
Street: Dieselstr. 10
Place: D-42781 Haan
Telephone: +49 2129 5568-0

Telephone: +49 2129 5568-0 Telefax: +49 2129 5568-282

e-mail: info@bohle.de

Contact person: Dr. Martin Schade Telephone: +49 2129 5568-300

e-mail: MSDS@bohle.de Internet: www.bohle.com

Responsible Department: Chemie

1.4. Emergency telephone Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate 2-hydroxyethyl methacrylate acrylic acid, prop-2-enoic acid tert-butyl perbenzoate maleic acid

Signal word: Danger



according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 2 of 13

Pictograms:







Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Methacrylate/Acrylate resin(s).



according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 3 of 13

Hazardous components

CAS No	Chemical name		Quantity	
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)	•	
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]he	pt-2-yl acrylate		<50 %
	227-561-6		01-2119957862-25	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. H319 H317 H335 H400 H410	1, STOT SE 3, Aquatic Ad	cute 1, Aquatic Chronic 1; H315	
73324-00-2	Urethane acrylate			<25 %
	615-966-4		-	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319)		
868-77-9	2-hydroxyethyl methacrylate			<25 %
	212-782-2	607-124-00-X	01-2119490169-29	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens.	1; H315 H319 H317	·	
24650-42-8	2,2-dimethoxy-1,2-diphenylethan-1	<8,9 %		
	246-386-6		01-2120000336-73	
	Acute Tox. 4, STOT RE 2, Aquatic	Chronic 3; H302 H373 H4	112	
79-10-7	acrylic acid, prop-2-enoic acid	<5 %		
	201-177-9	607-061-00-8	01-2119452449-31	
	Flam. Liq. 3, Acute Tox. 4, Acute T H332 H312 H302 H314 H400	ox. 4, Acute Tox. 4, Skin (Corr. 1A, Aquatic Acute 1; H226	
614-45-9	tert-butyl perbenzoate			<1 %
	210-382-2		01-2119513317-46	
	Org. Perox. C, Acute Tox. 4, Skin I H332 H315 H317 H400 H412	rrit. 2, Skin Sens. 1, Aqua	tic Acute 1, Aquatic Chronic 3; H242	
110-16-7	maleic acid			<1 %
	203-742-5	607-095-00-3	01-2119488705-25	
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit.			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
5888-33-5	227-561-6	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	<50 %
	dermal: LD50 = Aquatic Chronic	= >5000 mg/kg; oral: LD50 = >5000 mg/kg	
868-77-9	212-782-2	2-hydroxyethyl methacrylate	<25 %
	dermal: LD50 =	= >5000 mg/kg; oral: LD50 = 5050 mg/kg	
24650-42-8	246-386-6	2,2-dimethoxy-1,2-diphenylethan-1-one	<8,9 %
	dermal: LD50 =	= >5000 mg/kg; oral: LD50 = >1694 mg/kg	
79-10-7	201-177-9	acrylic acid, prop-2-enoic acid	<5 %
	I	50 = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 oral: LD50 = 500 mg/kg	
614-45-9	210-382-2	tert-butyl perbenzoate	<1 %
	1	E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = al: LD50 = 4838 mg/kg	
110-16-7	203-742-5	maleic acid	<1 %
	dermal: LD50 =	= 1560 mg/kg; oral: LD50 = 1090 mg/kg	



according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 4 of 13

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

Get medical advice/attention if you feel unwell.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If symptoms persist, call a physician.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting. Immediately give large quantities of water to drink. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Irritation to respiratory tract

Skin contact: May cause an allergic skin reaction.

Eye contact : Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

water spray, dry powder, foam, carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Carbon monoxide, nitrogen oxides (NOx)

5.3. Advice for firefighters

Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear personal protection equipment (refer to section 8).

Provide adequate ventilation.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Other information

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Ensure adequate ventilation.



according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 5 of 13

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid contact with skin and eyes.

Do not eat, drink or smoke when using this product.

Ensure adequate ventilation.

Advice on protection against fire and explosion

No special technical protective measures required.

Advice on general occupational hygiene

Wash hands before breaks and after work. When using do not eat, drink or smoke.

Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

Further information on handling

Avoid: UV-radiation/sunlight

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up.

Recommended storage temperature 5 - 25°C. Keep away from direct sunlight.

7.3. Specific end use(s)

adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
79-10-7	Acrylic acid	10	29		TWA (8 h)	WEL
		20	59		STEL (1 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate			
Worker DNEL, long-term		dermal	systemic	1,39 mg/kg bw/day
79-10-7	acrylic acid, prop-2-enoic acid			
Worker DNEL,	long-term	inhalation	systemic	30 mg/m³
Worker DNEL,	Worker DNEL, acute		systemic	30 mg/m³
Worker DNEL, long-term		inhalation	local	30 mg/m³
Worker DNEL,	Worker DNEL, acute		local	30 mg/m³



according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 6 of 13

PNEC values

CAS No	Substance		
Environmenta	invironmental compartment		
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate		
Freshwater		0,00092 mg/l	
Marine water		0,000092 mg/l	
Freshwater s	ediment	0,145 mg/kg	
Marine sediment		0,0145 mg/kg	
Micro-organisms in sewage treatment plants (STP)		2 mg/l	
Soil		0,0285 mg/kg	
79-10-7	acrylic acid, prop-2-enoic acid		
Freshwater		0,003 mg/l	
Freshwater (intermittent releases)		0,0013 mg/l	
Marine water		0,0003 mg/l	
Freshwater sediment		0,0236 mg/kg	
Marine sediment 0,		0,00234 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapour. To follow: Occupational exposure limit values

Individual protection measures, such as personal protective equipment

Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Recommended material: NBR (Nitrile rubber), VITON Unsuitable material: Natural fibres (e.g. cotton)

Skin protection

Wear suitable protective clothing.

Respiratory protection

Usually no personal respirative protection necessary. When using do not eat, drink or smoke. In case of inadequate ventilation wear respiratory protection. Full-/half-/quarter-face masks (EN 136/140)

Respirator with filter for organic vapour. Recommended Filter type: A (P2)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: characteristic

Test method

Print date: 04.07.2023

Flash point: > 100 °C

pH-Value (at 21 °C): 2,5 5% emulsion

Water solubility: not determined Density (at 25 °C): 1,1 g/cm³

9.2. Other information

Information with regard to physical hazard classes

Print date: 04.07.2023



Safety Data Sheet

according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 7 of 13

Explosive properties

None.

Other safety characteristics

Solvent content: 0,0% Viscosity / dynamic: 900 mPa·s (at 23 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Light / UV-radiation/sunlight Oxidising agent, strong

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep cool. Protect from sunlight. Heat, flames and sparks.

In case of light influence: Polymerisation

10.5. Incompatible materials

Reducing agent, strong. Oxidising agent, strong strong acids and strong bases

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

Thermal decomposition can lead to the escape of irritating gases and vapours. Carbon monoxide (CO),

Carbon dioxide (CO2), Hydrocarbons

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation



according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 8 of 13

Acute toxicity

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate							
	oral	LD50 mg/kg	>5000	Rat				
	dermal	LD50 mg/kg	>5000	Rabbit				
868-77-9	2-hydroxyethyl methacry	late						
	oral	LD50 mg/kg	5050	Rat				
	dermal	LD50 mg/kg	>5000	Rabbit				
24650-42-8	2,2-dimethoxy-1,2-diphe	nylethan-1-	one					
	oral	LD50 mg/kg	>1694	Rat				
	dermal	LD50 mg/kg	>5000	Rat				
79-10-7	acrylic acid, prop-2-enoic acid							
	oral	LD50 mg/kg	500	Rat				
	dermal	LD50 mg/kg	1100	Rat				
	inhalation (4 h) vapour	LC50	11 mg/l	Rat				
	inhalation dust/mist	ATE	1,5 mg/l					
614-45-9	tert-butyl perbenzoate							
	oral	LD50 mg/kg	4838	Rat				
	dermal	LD50 mg/kg	3817	Rabbit				
	inhalation vapour	ATE	11 mg/l					
	inhalation dust/mist	ATE	1,5 mg/l					
110-16-7	maleic acid							
	oral	LD50 mg/kg	1090	Rat	OECD 401			
	dermal	LD50 mg/kg	1560	Rabbit				

SECTION 12: Ecological information

12.1. Toxicity



according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 9 of 13

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate								
	Acute fish toxicity	LC50 mg/l	0,704	96 h	Danio rerio (zebrafish)	OECD 203			
	Crustacea toxicity	NOEC mg/l	0,092	21 d	Daphnia magna (Big water flea)				
868-77-9	2-hydroxyethyl methacryla	ate							
	Acute fish toxicity	LC50	227 mg/l	96 h	Pimephales promelas				
24650-42-8	2,2-dimethoxy-1,2-diphen	ylethan-1-o	ne						
	Acute fish toxicity	LC50	6 mg/l	96 h	Lepomis macrochirus (Bluegill)				
	Acute algae toxicity	ErC50 mg/l	0,17	72 h	Scenedesmus subspicatus				
	Acute bacteria toxicity	(EC50 mg/l)	>100	3 h	Activated sludge				
614-45-9	tert-butyl perbenzoate								
	Acute fish toxicity	LC50	1,6 mg/l	96 h	Danio rerio (zebrafish)	OECD 203			
	Acute algae toxicity	ErC50	1,3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD 201			
	Acute crustacea toxicity	EC50	11 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202			
110-16-7	maleic acid								
	Acute fish toxicity	LC50	75 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)				
	Acute algae toxicity	ErC50 mg/l	74,35	72 h	Pseudokirchneriella subcapitata	OECD 201			
	Acute crustacea toxicity	EC50 mg/l	42,81	48 h	Daphnia magna (Big water flea)	OECD 202			

12.2. Persistence and degradability

OAO NI-					
CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate				
		57%	28		
614-45-9	tert-butyl perbenzoate				
	aerob	70%	28		
	Readily biodegradable, according to appropriate OECD test.				

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	
5888-33-5	5888-33-5 Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	
868-77-9	2-hydroxyethyl methacrylate	0,47
24650-42-8	2,2-dimethoxy-1,2-diphenylethan-1-one	3,42
79-10-7 acrylic acid, prop-2-enoic acid		0,35
614-45-9	tert-butyl perbenzoate	3
110-16-7	maleic acid	-1,3



according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 10 of 13

BCF

CAS No	Chemical name	BCF	Species	Source
110-16-7	maleic acid	<10		

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Consult the appropriate local waste disposal expert about waste disposal.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(@5888.33.5Pan, @0079.10.7Pan)

14.3. Transport hazard class(es):

14.4. Packing group:
Hazard label:

9

9

Ш



Classification code: M6

Special Provisions: 274 335 375 601

Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 90



according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 11 of 13

Tunnel restriction code:

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(@5888.33.5Pan, @0079.10.7Pan)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label:

9

Classification code: M6

Special Provisions: 274 335 375 601

Limited quantity: 5 L Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate, acrylic acid,

prop-2-enoic acid)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label:

9

Ш

Special Provisions: 274, 335, 969

Limited quantity: 5 L
Excepted quantity: E1
EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate, acrylic acid,

prop-2-enoic acid)

14.3. Transport hazard class(es):
14.4. Packing group:

Hazard label:



Ш

Special Provisions: A97 A158 A197

Limited quantity Passenger: 30 kg G
Passenger LQ: Y964
Excepted quantity: E1

IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards



according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 12 of 13

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: @5888.33.5Pan, @0079.10.7Pan

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC): 0 %

0 g/l

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Classification for mixtures and used evaluation method according to GB CLP Regulation

- indemonstration in the contraction in the contrac				
Classification	Classification procedure			
Skin Irrit. 2; H315	Calculation method			
Eye Dam. 1; H318	Calculation method			
Skin Sens. 1; H317	Calculation method			
STOT SE 3; H335	Calculation method			
Aquatic Acute 1; H400	Calculation method			
Aquatic Chronic 1; H410	Calculation method			

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be



according to UK REACH Regulation

UV Adhesive VERIFIX B 682-T

Revision date: 04.07.2023 Product code: BO5209394 Page 13 of 13

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)