

Safety Data Sheet

according to UK REACH Regulation

BriteGuard Surface SEALER X

Revision date: 05.05.2022

Product code: BO5825000

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1. Product identifier

BriteGuard Surface SEALER X

Further trade names

BO 5820500, 500 ml

BO 5825000, 5 l

1.2. Relevant identified uses of the substance or mixture and uses advised against
Use of the substance/mixture

Solvent-borne coatings

1.3. Details of the supplier of the safety data sheet

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Dr. Martin Schade	Telephone: +49 2129 5568-300
e-mail:	MSDS@bohle.de	
Internet:	www.bohle.com	
Responsible Department:	Chemie	

1.4. Emergency telephone number: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification
2.1. Classification of the substance or mixture
GB CLP Regulation

Flam. Liq. 2; H225
 Asp. Tox. 1; H304
 Skin Irrit. 2; H315
 Eye Irrit. 2; H319
 Repr. 2; H361f
 STOT SE 3; H336
 Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements
GB CLP Regulation
Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol
 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
 octamethylcyclotetrasiloxane

Signal word: Danger

Pictograms:

Hazard statements

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.

Safety Data Sheet

according to UK REACH Regulation

BriteGuard Surface SEALER X

Revision date: 05.05.2022

Product code: BO5825000

Page 2 of 11

H319	Causes serious eye irritation.
H361f	Suspected of damaging fertility.
H336	May cause drowsiness or dizziness.
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P235	Keep cool.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.

Labelling of packages where the contents do not exceed 125 ml
Signal word: Danger

Pictograms:

Hazard statements

H361f-H336-H304

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Chemical characterization

Solvent-borne coatings

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			>50 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			<20 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
556-67-2	octamethylcyclotetrasiloxane			<25 %
	209-136-7	014-018-00-1	01-2119529238-36	
	Flam. Liq. 3, Repr. 2, Aquatic Chronic 1; H226 H361f H410			
110-54-3	n-hexane			<0,5 %
	203-777-6	601-037-00-0	01-2119480412-44	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H373 H304 H411			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

BriteGuard Surface SEALER X

Revision date: 05.05.2022

Product code: BO5825000

Page 3 of 11

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	>50 %
		inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 13400 mg/kg; oral: LD50 = 4570 mg/kg	
64742-49-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	<20 %
		inhalation: LC50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
556-67-2	209-136-7	octamethylcyclotetrasiloxane	<25 %
		M chron.; H410: M=10	
110-54-3	203-777-6	n-hexane	<0,5 %
		STOT RE 2; H373: >= 5 - 100	

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

Take off immediately all contaminated clothing.

After inhalation

Move to fresh air. Consult a physician after significant exposure. If victim is unconscious but breathing: Victim to lie down in the recovery position, cover and keep him warm. Call a physician immediately.

After contact with skin

Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists, consult a specialist.

After ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Give sodium sulfate as laxative (1 tablespoon in 1 glass of water) with plenty of activated coal.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures
5.1. Extinguishing media
Suitable extinguishing media

water spray, alcohol-resistant foam, dry chemical, carbon dioxide (CO₂)

Unsuitable extinguishing media

high volume water jet

5.2. Special hazards arising from the substance or mixture

In use may form flammable/explosive vapour-air mixture.
Fire may cause evolution of: Carbon monoxide, Carbon dioxide)

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Standard procedure for chemical fires.

Additional information

Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

Safety Data Sheet

according to UK REACH Regulation

BriteGuard Surface SEALER X

Revision date: 05.05.2022

Product code: BO5825000

Page 4 of 11

6.1. Personal precautions, protective equipment and emergency procedures
General advice

Use personal protective equipment. Keep people away from and upwind of spill/leak.
 Ensure adequate ventilation.
 Keep away from heat and sources of ignition.
 Avoid contact with skin and eyes. Do not breathe vapour.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.
 Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.
 Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up
Other information

Provide adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7
 Personal protection equipment: see section 8
 Disposal: see section 13

SECTION 7: Handling and storage
7.1. Precautions for safe handling
Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations.
 Provide room air exhaust at ground level.
 Avoid formation of aerosol. Do not breathe vapour/aerosol.
 Avoid contact with the skin and the eyes.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition. Do not smoke.

Advice on general occupational hygiene

Avoid contact with skin, eyes and clothing. Provide adequate ventilation. Take off all contaminated clothing immediately. Keep away from food, drink and animal feedingstuffs. When using do not eat or drink. Do not smoke. Wash hands before breaks and at the end of workday.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
110-54-3	n-Hexane	20	72		TWA (8 h)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

BriteGuard Surface SEALER X

Revision date: 05.05.2022

Product code: BO5825000

Page 5 of 11

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol		
Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	89 mg/m ³
Worker DNEL, long-term	inhalation	systemic	500 mg/m ³
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Worker DNEL, long-term	dermal	systemic	773 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	2035 mg/m ³
Consumer DNEL, long-term	dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term	oral	systemic	699 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment	Value	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater	140,9 mg/l	
Freshwater (intermittent releases)	140,9 mg/l	
Marine water	140,9 mg/l	
Freshwater sediment	552 mg/kg	
Marine sediment	552 mg/kg	
Micro-organisms in sewage treatment plants (STP)	2251 mg/l	
Soil	28 mg/kg	

8.2. Exposure controls
Appropriate engineering controls

Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached. However it is the duty of the user to verify this and follow given exposure limits at the workplace.

Individual protection measures, such as personal protective equipment
Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber) $\geq 0,5\text{mm}$, NBR (Nitrile rubber) $\geq 0,35\text{mm}$

Breakthrough time: ≥ 480 min.

Skin protection

impervious clothing

Respiratory protection

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

BriteGuard Surface SEALER X

Revision date: 05.05.2022

Product code: BO5825000

Page 6 of 11

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
 Colour: clear
 Odour: alcoholic

Test method

Changes in the physical state

Melting point/freezing point: -89,5 °C
 Boiling point or initial boiling point and boiling range: 82 °C
 Flash point: 12 °C

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: 2 vol. %
 Upper explosion limits: 12 vol. %
 Auto-ignition temperature: 425 °C

Self-ignition temperature

not auto-flammable

pH-Value (at 20 °C): 3
 Viscosity / dynamic: (at 20 °C) 2,4 mPa·s
 Water solubility: (at 20 °C) soluble
 Vapour pressure: (at 20 °C) 48 hPa
 Density (at 20 °C): 0,79 g/cm³

9.2. Other information

Other safety characteristics

Solvent content: 83%
 Solid content: 5%

Further Information

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal processing.

10.2. Chemical stability

No decomposition if used as directed.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4. Conditions to avoid

Keep away from heat and sources of ignition.
 Take action to prevent static discharges.

10.5. Incompatible materials

strong acids and oxidizing agents

Safety Data Sheet

according to UK REACH Regulation

BriteGuard Surface SEALER X

Revision date: 05.05.2022

Product code: BO5825000

Page 7 of 11

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in GB CLP Regulation
Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 mg/kg	4570	Rat	
	dermal	LD50 mg/kg	13400	Rabbit	
	inhalation (4 h) vapour	LC50	30 mg/l	Rat	
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50 mg/kg	>5000	Rat	
	dermal	LD50 mg/kg	>2000	Rat	
	inhalation (4 h) vapour	LC50	>20 mg/l	Rat	

11.2. Information on other hazards
Other information

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

SECTION 12: Ecological information
12.1. Toxicity

Safety Data Sheet

according to UK REACH Regulation

BriteGuard Surface SEALER X

Revision date: 05.05.2022

Product code: BO5825000

Page 8 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	>2000	72 h	Desmodesmus subspicatus	
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane					
	Acute fish toxicity	LC50 mg/l	11,4	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203
	Acute algae toxicity	ErC50 mg/l	30-100	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50	3 mg/l	48 h	Daphnia	OECD 202
	Fish toxicity	NOEC mg/l	2,04	28 d	Oncorhynchus mykiss (Rainbow trout)	
	Algae toxicity	NOEC	3 mg/l	3 d	Pseudokirchneriella subcapitata	OECD 201
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna (Big water flea)	OECD 211
110-54-3	n-hexane					
	Acute fish toxicity	LC50	2,5 mg/l	96 h	Pimephales promelas	Geiger et al. 1990

12.2. Persistence and degradability

Readily biodegradable, according to appropriate OECD test.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	OECD 301F	98%	28		
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential
Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	-0,16
110-54-3	n-hexane	3,9

12.4. Mobility in soil

The product evaporates readily.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Water hazard class 3: highly water endangering

Do not let product enter drains.

SECTION 13: Disposal considerations

Safety Data Sheet

according to UK REACH Regulation

BriteGuard Surface SEALER X

Revision date: 05.05.2022

Product code: BO5825000

Page 9 of 11

13.1. Waste treatment methods
Disposal recommendations

In accordance with local and national regulations.

List of Wastes Code - residues/unused products

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures; hazardous waste

List of Wastes Code - used product

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures; hazardous waste

List of Wastes Code - contaminated packaging

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); plastic packaging

Contaminated packaging

Non-contaminated packages may be recycled.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 601
 Limited quantity: 1 L
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 601
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1219

Safety Data Sheet

according to UK REACH Regulation

BriteGuard Surface SEALER X

Revision date: 05.05.2022

Product code: BO5825000

Page 10 of 11

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: -
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: Isopropanol
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A180
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

none

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
 octamethylcyclotetrasiloxane

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 29, Entry 40, Entry 70, Entry 75

2004/42/EC (VOC): 83 % (656 g/l)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

Safety Data Sheet

according to UK REACH Regulation

BriteGuard Surface SEALER X

Revision date: 05.05.2022

Product code: BO5825000

Page 11 of 11

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information
Changes

This data sheet contains changes from the previous version in section(s): 2.

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361f	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)